

CA-PVN/PCK CCD Camera

Feature

- Direct Plugged-in design right on the side of the PV series unit for instant operation
- Different alternation for connecting via an standard attached AV cable for more flexible use
- Powered by the PV recording device directly for more compact application
- Full range of our PV series recording device could work with perfectly



Specification

Item Number	CA-PVNCK	CA-PVPCK
Video System	NTSC	PAL
Picture Element	(H)512x(V)492	(H)512x(V)492
Resolution (H)	330 TV Line	
CCD Image Sensor	1/4 Interline CCD	
S/N Ratio	46 db (MIN)	
MIN Illumination	0.5 Lux / F2.3	
Electronic Shutter	1/60~1/120,000	1/50~1/120,000
A.G.C.	+24 dB MAX	
Video Output	1.0Vp-p Composite at 75 ohm	
Audio Output	2Vp-p(MAX) 10KHz ohms Impedance	
MIC Sensitivity	59 dB +/-13 dB	
Lens	4.3 mm	
Angel of View	78 Degree	
Power Supply Voltage	5V +/-0.5V	
Power Supply Current	150mA	
Dimension(Incl Lens)	32(W) x 22(H) x 11(T) mm	
Weight	15g	



Connected /w the PVR via the attached Cable



Direct plugged with PVR

*Specification & appearance may be subjected to change without notice

Standard Shipping Package

- CA-PVN/PCK Main Unit. * 1
- AV in & DC5V out combo jack Cable * 1
- 4P3R AV Switching Cable * 1
- Operation Manual * 1

Matched Working Items

- Whole PV series recording device